


SOUND TRANSMITTER

Model : TR-SLT1A4

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

SOUND LEVEL TRANSMITTER

Model : TR-SLT1A4

Measure Range	<p><i>Range 1 :</i> 30 - 80 dB</p> <p><i>Range 2 :</i> 50 - 100 dB</p> <p><i>Range 3 :</i> 80 - 130 dB</p>
Output	<p>4 - 20 mA</p> <p><i>Range 1 :</i> 30 dB:7.69 mA 80 dB:13.84mA</p> <p><i>Range 2 :</i> 50dB:10.15 mA 100dB:16.3mA</p> <p><i>Range 3 :</i> 80dB:13.84mA 130 dB:20 mA</p>
External Adjustment	94 dB Cal. VR
Power Supply	90 - 260 ACV 50 Hz/60 Hz
Operation Temperature	0 - 50 °C 32 - 122 °F
Operation Humidity	Less than 80 %RH
Accessory Included	Sound level Probe
Optional Accessories	Sound calibrator SC-941 (94 dB) SC-942 (94 dB/114 dB)
Mounting Case	Din rail or Wall ABS plastic
Others	Separate probe

* Appearance and specifications listed in this brochure are subject to change without notice.